



Transport solution

Duotank Transport tanks

Transport solutions



Brewery Fresh Beer

Brewery Fresh Beer at any location at any time, is possible with the transport tanks from Duotank. Good isolation keeps the beer at a desired temperature.

Transport tanks

With the transport tanks of Duotank you have one solution to transport and store your beer. The tanks are insulated to make sure that your beer stays cool during transport. The tanks have (optional for vertical tank) a cooling coil so that you can even use them for your local events or as an extra storage tank outside your cold room. Due to the unique Bag-In-Tank concept it is possible to store your beer for a longer time even if the tank is half full.

You can transport beer from the brewery to the bar in the transport tank. The beer can easily be pushed over with a connection hose and compressed air. If you want to further automate the delivery process the Standard Delivery Unit (SDU) or Compact Delivery Unit (CDU) are available.

The horizontal transport tank has a full frame around the tank, shielding it from possible transport damage and making it possible to stack the tanks by using a standard forklift. Optionally, the tanks can be equipped with heavy duty transport wheels, making it possible to move the tank without a forklift.

There is also a vertical transport tank available with an integrated frame.



Get in touch:

Petunialaan 5,
5582 HA, Waalre, The Netherlands

Tel. +31 (0)40 221 22 72 / Fax. +31 (0)40 221 22 36

Email. sales@duotank.nl



Transport tanks



Transport tanks

Horizontal

Tank size	2,5 HL	5 HL	10HL
Tank type	Double walled stainless steel, insulated with cooling coil		
Weight	Ca. 175 kg	Ca. 200 kg	Ca. 275 kg
Dimensions (L * W * H)	1397 * 762 * 864 mm	1941 * 886 * 936 mm	2386 * 1048 * 1100 mm
Outlet	NW 25	NW 25	NW 25
Frame Material	Stainless steel (304/1.4301)		
Including	- Safety valve 3/4"		
Optional	- Heavy duty wheels - Piercing unit		

Vertical

Tank size	5 HL
Tank type	Integrated stainless steel tank, insulated with or without cooling coil
Weight	Ca. 250 kg
Dimensions (L * W * H)	938 * 878 * 1789 mm
Outlet	NW 25
Frame material	Stainless steel (304/1.4301)
Including	- Safety valve 3/4"
Optional	- Heavy duty wheels - Piercing unit

Important

All transport tanks are delivered **without** brand signs